



- NOTES:
- TANK MUST MEET ALL APPLICABLE SPECIFICATIONS OF NSF/ANSI 044 STANDARD, LATEST REVISION.
 - OPERATING SPECIFICATIONS:
 - A. MAXIMUM WORKING PRESSURE - 150 PSI (10.5BAR)
 - B. TEMPERATURE RANGE - 34-120° F(1-49°C)
 - C. MAXIMUM VACUUM - 5"Hg (127mm Hg)
 - VISUAL LINER INSPECTION
 - A. NO MORE THAN 10 INTERNAL OR EXTERNAL BLEMISHES OR BURNT DEBRIS.
 - B. NO INTERNAL OR EXTERNAL BLEMISHES OR BURNT DEBRIS LARGER THAN 3×3mm.
 - C. NO INTERNAL BLEMISHES OR BURNT DEBRIS ALLOWED.
 - ALL GLASS STRANDS FROM FIBERGLASS LINER TO BE BONDED AND COVERED.
 - SURFACE TO BE FREE OF NICKS, SCRATCHES, RESIN AND GLASS.
 - SURFACE FINISH.
 - DIMENSIONS IN PARENTHESIS ARE REFERENCE ONLY.
 - DIMENSIONS IN SQUARE PARENTHESIS ARE INCH UNIT.

MODEL	A			VOLUME		DOME VOLUME		WEIGHT			
	mm	inch	+/-	liters	U.S. gal	liters	U.S. gal	kg	LBS		
9x48	1226	48.27	5	44.6	11.78	1.57	0.88	0.23	0.03	6.75	14.85

1		THIS DRAWING IS TREATED COMPUTING WITH THE CHINESE VERSION		DESCRIPTION OF CHANGES:		SIGNATURE:		2008/07/21	
VERSION NO.		REPRESENTAL PLASTIC SHRINKAGE (IF NECESSARY):		SCALE		MATERIAL		MODEL	
SIGNATURE		NAME		DATE		WAVE CYBER (SHANGHAI) CO., LTD.		DESCRIPTION	
DESIGN		INSPECTION		APPROVAL		1 : 4		SMOOTHNESS	
THIS PRODUCT DRAWING CAN NOT BE COPIED AND/OR USED WITHOUT PRIOR WRITTEN APPROVAL OF WAVE CYBER.		PROJECTION		COMPUTER CODE		DRAWING NO.		VERSION NO.	
DO NOT MEASURE THE DIMENSIONS.		UNIT: MM		TOTAL PAGE: 1		114091-01-00		1	