


MODEL	A (mm)	B (mm)	C (mm)	VOLUME	WEIGHT (kg)	AREA (INSIDE)
14×65	1858±6	1392.5	992	148L	16	1.82 m ²

NOTE:

1. TEST METHOD FOR VESSEL PERFORMANCE COMPLIES WITH NSF/ANSI44-2002 "NSF INTERNATIONAL STANDARD/AMERICAN NATIONAL STANDARD"
2. MAXIMUM WORKING PRESSURE:10.5Bar, WATER MEDIUM TEMPERATURE RANGE: 1°C-49°C; NOT APPLICABLE TO CORROSIVE LIQUID;
3. DIMENSIONAL TOLERANCE:SJ1372-78, GRADE 8.
4. TANK IS SUPPLIED WITH ADAPTOR:

- 1.5"NPT MALE ADAPTOR / 1¼" SOCKET ADAPTOR
- 1.5"BSP MALE ADAPTOR / 40mm SOCKET ADAPTOR



VERSION NO.	DESCRIPTION OF CHANGES:		SIGNATURE	DATE	
	REFERENTIAL PLASTIC SHRINKAGE (IF NECESSARY):				
SIGNATURE		WAVE CYBER (SHANGHAI) CO., LTD.			
NAME	DATE				
DESIGN	SCALE	MATERIAL	MODEL		
INSPECTION			DESCRIPTION		
APPROVAL	QUANTITY	WEIGHT	14"VESSEL (4"×4" inlet) (Threaded Side Inlets)		
THIS PRODUCT DRAWING CAN NOT BE COPIED AND/OR USED WITHOUT PRIOR WRITTEN APPROVAL OF WAVE CYBER.		PROJECTION	COMPUTER CODE	DRAWING NO.	VERSION NO.
				114144-00	0
DO NOT MEASURE THE DIMENSIONS.		UNIT: MM	TOTAL PAGE: 1		